

# **FUTURISTIC BIOTECHNOLOGY**

https://fbtjournal.com/index.php/fbt ISSN(E): 2959-0981, (P): 2959-0973 Vol 05 Issue 03, (July-Sep, 2025)



#### **Review Article**



Algae, Third-Generation Energy Source: A Comprehensive Review on Methods from Cultivation to Biodiesel Production

Noreen Iftikhar<sup>1</sup>, Javaria Ilyas<sup>1</sup>, Muhammad Ikram Ramzan<sup>1</sup>, Esha Asghar<sup>1</sup>, Areeba Manzoor<sup>1</sup> and Momina Afzal<sup>1</sup>

<sup>1</sup>Center of Excellence in Molecular Biology, University of the Punjab, Lahore, Pakistan

#### ARTICLE INFO

#### Keywords:

Algae, Biodiesel, Photo-bioreactor, Transesterification

#### How to Cite:

Iftikhar, N., Ilyas, J., Ramzan, M. I., Asghar, E., Manzoor, A., & Afzal, M. (2025). Algae, Third-Generation Energy Source: A Comprehensive Review on Methods from Cultivation to Biodiesel Production: Algae, Third-Generation Energy Source: Methods from Cultivation to Biodiesel Production. Futuristic Biotechnology, 5(3), 10-18. https://doi.org/10.54393/ fbt.v5i3.181

#### \*Corresponding Author:

Muhammad Ikram Ramzan Center of Excellence in Molecular Biology, University of the Punjab, Lahore, Pakistan ikramramzan5288@gmail.com

Received Date: 25<sup>th</sup> June, 2025 Revised Date: 9<sup>th</sup> August, 2025 Acceptance Date: 12th August, 2025 Published Date: 30<sup>th</sup> September, 2025

#### ABSTRACT

An increase in population growth has elevated the energy demand, and diminished fossil fuel sources. Their combustion releases carbon dioxide and contributes to environmental pollution. This has initiated intensive research to find alternative sources for economic and environmental sustainability. Amongst all, biodiesel originating from oil crops is a biodegradable, environmentfriendly substitute and has properties similar to fossil diesel. Algal sources are promising substrates that require only sunlight and water for oil production. They could fulfil global demand, reduce the use of petroleum-based diesel and have higher oil productivity than other oil-yielding crops. Therefore, the third-generation production of biodiesel through microalgae is the renewable choice to overcome the energy crisis. This review covers algal cultivation methods, including both open and closed systems, lipid-extracting techniques for taking out algal oil or lipids from microalgae, and biodiesel production by the transesterification process. This article aims to assist in selecting appropriate cultivation and extraction methods for biodiesel generation.

#### INTRODUCTION

Energy demand has been rising steadily over the past ten years, along with adverse environmental effects. Since fossil fuels are the main source of energy for the automobile industry, global warming and a rapid decline in the availability of natural resources are being observed. Previously, researchers have carried out research on firstand second-generation biofuel production methods, and their engine testing showed that the cultivation of the feedstocks used is unsustainable. However, a substantial reduction in the emission of nitrogen oxides was observed [1]. The growing concerns regarding climate change and the depletion of fossil fuel reserves have led to an increased focus on renewable and eco-friendly energy sources to preserve the beauty of the environment and address the depletion of natural resources [2]. One promising avenue for sustainable energy production is biofuels, which are derived from organic matter such as plants and algae. Amongst the various sources of biofuel, third-generation algal biomass has gained significant attention due to its high potential for efficient and environmentally friendly biofuel production [3]. Compared to first-generation (e.g., corn or sugarcane) and secondgeneration (e.g., lignocellulosic) biofuels, microalgae offer up to 58,700 L/ha/year of oil yield, significantly higher than

soybean (446 L/ha) or rapeseed (1,190 L/ha) [1]. Moreover, algal cultivation can occur on non-arable land with 95% lower freshwater use and up to 70% reduction in GHG emissions per MJ produced, as shown in recent LCA studies. Techno-economic analyses also suggest competitive production costs with continued optimization and integration of co-products [2, 3]. Algae can grow in diverse environments, including freshwater, seawater, and wastewater. However, this adaptability is straindependent-e.g., Dunaliella salina tolerates high salinity, while Chlorella vulgaris thrives in freshwater. Nutrient needs differ across strains, affecting lipid yields. In wastewater systems, growth is challenged by fluctuating COD/BOD, heavy metals, and microbial contamination, which hinder biomass productivity and require careful pretreatment and monitoring to maintain stable cultures [4-6]. This versatility enables algae production without competing for arable land [7], making it an attractive option for biofuel production without compromising food production. Algal sources are regarded as sustainable feedstocks due to their rapid growth rates and potential for biodiesel production. Moreover, many algal strains contribute to wastewater remediation through mechanisms such as nutrient uptake (e.g., nitrogen, phosphorus), heavy metal sequestration via biosorption, and reduction of chemical and biological oxygen demand (COD/BOD) by assimilating organic pollutants and supporting microbial communities involved in biodegradation [8]. Furthermore, algae have a remarkable ability to photosynthesize and convert sunlight into biomass at an unparalleled rate [9]. They can produce a high yield of biomass per unit area [10] compared to traditional crops, such as corn or soybeans, making algae a highly efficient feedstock for biofuel production. After cultivation, algal biomass is harvested and processed for the extraction of oil. The oil is converted into biodiesel through a chemical process called transesterification [11]. Biodiesel is the most sought-after biofuel due to its high biodegradability and environmentally friendly, non-toxic properties. Algal species are selected depending upon the percentage of the lipid content present in algal cells and the type of oil, hydrocarbons, and lipids to be extracted [10]. Biodiesel can be produced by both macroalgae and microalgae; the common algal species examined for the production of biodiesel are Thalassiosira pseudonana, Chlorella sp., Chlamydomonas reinhardtii, Phaeodactylum tricornutum, Isochrysis sp., and Dunaliella salina [12]. Some species of algae have a high content of lipids as much as 60% of their total weight. Triglycerides (TAGs) are commonly found in lipids that are stored in metabolites, storage products, and components of membranes [10]. The primary storage lipids in microalgae are triglycerides (TAGs) made during times of stressful conditions such as nitrogen starvation. They contain three fatty acids that are esterified to glycerol; consequently, they make the best raw materials for use in the transesterification process as a result of their fidelity in fatty acids and limited polarity. In contrast, TAGs make it possible to achieve a high percentage conversion to biodiesel (>95%) without the formation of undesirable byproducts, as is with phospholipids. Therefore, increased accumulation of TAGs will have a direct positive effect on biodiesel productivity and quality [13]. Studies have been conducted to compare the biodiesel production between macroalgae and microalgae, and it has been found that high biodiesel production is produced by using microalgae as a substrate due to the high growth rate of microalgae, which leads to better yield. Microalgae can produce large amounts of lipids; typically, 30% lipid content is present in algal cells, which increases the quantity of extracted oil that turns into biodiesel. Strain selection of microalgal strains depends on the availability of raw materials, optimization of growth and economic viability. Hossain et al. [14] compared the Oedogonium and Spirogyra algal species and found Oedogonium as a good source of biodiesel on one hand; and Spirogyra to yield more residual biomass after extraction. This proves that strain-specific lipid productivity and biomass profiles directly affect the amounts of biodiesel as well as process scalability [14]. Besides being environmentally friendly, algal biodiesel production in Pakistan could significantly boost the economy by utilizing 27-28 million acres of saline land, creating rural jobs, supporting energy independence, and generating up to 195 million PKR/year per 1-ton/day plant with a 4-year payback period[15].

This study aimed to discuss different suitable methods of algal cultivation, effective methods of oil extraction from algae using different techniques, possible effects on the economy by using biodiesel in transportation, and future perspectives.

#### Algal Cultivation System: Open Ponds

An open cultivation system is a method of growing microalgae in an open environment, typically in shallow ponds, raceway ponds, or other open containers. This growth method allows for natural sunlight exposure and atmospheric gas exchange, resulting in the production of algal biomass. The open cultivation system is considered the most traditional and cost-effective approach for largescale microalga production [1]. Open systems account for approximately 98% of overall biomass production. Due to the high growth rate of microalgae, which reaches 1.5-2.0 grams per liter per day, they can produce 15 to 20 tons of dry biomass per acre per year, with oil comprising 50 to 60% of the dry weight in high-yielding strains; thus, it is economically feasible to produce biodiesel using microalgae [16]. Natural resources like concrete and rammed earth can be used for building an open pond system. The main disadvantage of such reactors is the gradual degradation of the light-transmitting walls, among others, because of the deposition of biofilm on the inner surface. Compared to open ponds, closed ponds are made of acrylics and are more expensive [17]. Open pond systems are cost-effective but limited by environmental stress; most algae grow best between 20-30°C and light intensities below 400 µmol m<sup>-2</sup> s<sup>-1</sup>, while thermotolerant strains like Chlorella sp. GD M4 can withstand up to 49°C and high irradiance, sustaining biomass yield [18]. Accumulation of unwanted contaminants due to fungal growth and algae invasions, uneven distribution of light, and an open pond's inability to hold photosensitive dark zones (as light can only penetrate to a particular depth) are also causes for concern [1]. Phytoremediation using Chlorella species has proved to be successful through pilot-scale tests over the recent past. A techno-economic analysis of a tubular photo-bioreactor treating agricultural centrate wastewater with Chlorella sp. yielded 34.6 g/m<sup>2</sup>/day (TSS) and removal of 70% COD, 61% TKN, and 61% phosphorus [19]. Closed systems overcome numerous disadvantages of open ponds [20]. Most algal biomass is produced in open cultivation systems; such systems are also known as raceway or circular ponds [1]. Although raceway ponds with paddle wheels overcame some limitations of the earlier designs, such as poor scaling of the system and the possibility of contamination [1, 20], mixing and yield were enhanced [17, 21].

This man-made closed system not only reduces contamination during the manufacture of costly metabolites but also prevents evaporation loss, which is a major concern in open systems. Photobioreactors are artificial systems for the continuous cultivation of microalgal strains by recirculation at optimum pH, temperature and light. Light path length is critical, as shorter paths (typically <30 mm) reduce self-shading and improve light utilization efficiency. Effective mixing regimes (e.g., airlift or mechanical agitation) enhance gas-liquid mass transfer and prevent biomass sedimentation. Mass transfer coefficients are equally important to avoid oxygen accumulation and ensure CO2 availability, directly influencing productivity. A comparative analysis by Carvalho et al. highlights how reactor geometry, mixing strategy, and light penetration together impact overall reactor performance [22]. Most studies report biomass productivities in the range of 20-35 g/m<sup>2</sup>/day under optimal conditions. However, a huge temperature rise is a major pitfall that can be easily controlled by agitation and modifying the open and closed system organization that upgrades the biomass production [1]. Future modifications of closed PBRs are based on their geometric configurations, like vertical, horizontal, helical

and flat panel PBR. As compared to open systems, these PBRs have 5-10 times higher efficiency but are uneconomical [23]. Although PBRs are expensive, they also have many advantages that are given below: (1) Reduce or eliminate external algae, fungi or amoeba contamination, (2) Minimize the evaporation loss to save backup water for open ponds, (3) All the parameters e.g., nutrients and gases levels are supervised and maintained, (4) Biomass can be produced at night by using LED systems which work like natural sunlight. Although artificial lights, especially LEDs, allow biomass production to continue at night by imitating photosynthetically active radiation (PAR), they also make the cost of operation highly energydependent. It has been found that artificial lighting may comprise as much as 50-270% of the total energy input in closed photo-bioreactors [22]. Conversely, solar-based systems are more energy-efficient and environmentally viable, especially when evaluated using life cycle analysis [1]. Photobioreactors (PBRs), in the form of transparent glass or acrylic, take the form of tubular geometries and are adapted to sunlight exposure with different modes of operation that enhance algal productivity [23]. The types include vertical (airlift, bubble column) [16, 14], horizontal [16], helical [22], and flat-plate PBRs [22]. Stirring implies the utilization of bubbling/swirling, and PVC/PE PBRs can deteriorate rapidly [24], Figure 1.




Figure 1: Algae Cultivation Systems: Open and Closed Pond Systems

## **Pre-processing of Cultivated Microalgae**

Microalgal biomass can be wet (70–80 wt.% water), and preprocessing is necessary to dehydrate before lipid extraction because the additional moisture adversely affects the efficiency of solvents [25]. The solvent penetration is improved by the drier, which enlarges the surface area, but the cost of drying biodiesel is increased by 35%; drying with an oven is better than drying in the sun because the drying process can be controlled [17]. Flocculation, sedimentation, centrifugation, membrane filtration, and air flotation have been identified as dewatering processes, and they are determined depending

on the biomass load [26]. Centrifugation is required in small-scale because of the cost [25], and membrane filtration is motorized by pressure [21]. Flocculation and coagulation are similar phenomena of charge- or coagulant-mediated aggregation, and air flotation relies on bubbles to float particles [27].

#### **Lipid Extraction Methods**

Lipids are extracted after harvesting and lyophilizing the microalgae. The fundamental principles of lipid extraction from microalgal cells include easy scalability and minimal disturbance to lipid components. Common methods are solvent extraction and supercritical fluid extraction [28]. Technological advancements have led to many new methods of extraction that are eco-friendly (Figure 2).




Figure 2: Different Lipid Extraction Techniques

In 1879, the first introduced method of lipid extraction was the Soxhlet method. It was used to measure the total lipid quantity in milk [29], and it has since been steadily driven in the domains of pharmaceuticals, food, and other industries. This method uses a Soxhlet extractor for extraction. In Soxhlet extraction, rather than rupturing the cells to release lipids, the process relies on diffusion across the cell wall. The choice of solvent is critical; various solvents and their combinations have been evaluated, with polarity ranging from 0.1(petroleum ether and n-hexane) to 5.2 (ethanol) for extracting lipids from microalgae [30]. According to the data, chloroform, n-hexane, and ethanol yield high lipid contents, whereas acetone yields the least [31]. Due to its low cost, simple operations, and high yield, the Soxhlet method remains widely used in research and industry. However, it presents certain limitations, such as the use of hazardous solvents (e.g., carcinogenic benzene, less-toxic hexane), high reagent consumption, and being time-consuming [32]. The Folch and Bligh, and Dyer methods are well applied in the extraction of animal, plant, and microalgal samples. The major differences lie in the ratios of solvents: Folch is 2:1:0.7 and Bligh and Dyer 1:2:0.8 (chloroform: methanol: water) [33]. Both procedures are efficient; however, when it comes to microalgae, rigidity in cell walls is a problem that can create the risk of loss of lipids during the process of disruption [28]. Bligh and Dyer are more cash-efficient and safer. Supercritical  $\rm CO_2$  extraction and greener adjustments are long-established alternatives with better performance [34, 35].

Traditionally, solvent-free expelled pressing involves highpressure hacks scaling up dried algal biomass to rupture. allowing extraction of oil: 70-75% depending on morphology and strain [36]. Nonetheless, it is expensive because it requires a lot of energy, drying (30% of the production cost), and maintenance of the equipment [26], even though it extracts high-quality oil with minimal oxidation [35]. Laboratory-scale bead beating, where vibratory action rapidly agitates the solution in the presence of small beads, is an efficient cell disruptor by grinding or collision of cells. It is economical and does not dry out, and it also maintains heat-sensitive biomolecules through cooling jackets [35]. Ultrasonication has been proposed to increase both cell lysis and release of lipids due to cavitation and acoustic streaming [37, 38], but its application is energy- and reactor-type-dependent and cell type-dependent [39, 21]. First described in 1986 [36], microwave (MW) extraction applies a variable electric field to the sample, leading to rupture of the cells via internally generated pressures and electroporation, to effect extraction in as little as 15-20 minutes [40]. Despite its effectiveness, it has issues of scalability, heating uniformity, and high maintenance [41]. Electroporation involves using electrical voltages to raise the permeability of the membranes and has advantages such as low energy requirement, reduced contaminants, preservation of membranes, and low energy [36, 25]. Osmotic pressure, as a means of rupturing the cells with hyper- or hypo-osmotic stress due to salt, scales well and has the potential to be a low-equipment process that needs additional speciesspecific research [21, 25]. There is an opportunity to use ionic liquids, or so-called green solvents and anion-cation pairs, which can be tuned to achieve environmentally friendly extraction [35, 36]. The method can be used instead of toxic solvents, and future studies are required to prove the method. The enzymatic extraction allows the removal of lipid through the rupture of the algal cell walls using special enzymes, which is precise but speciesspecific and depends on the composition of the lipid and low temperatures (36; 25). Supercritical CO<sub>2</sub> also involves the extraction of selective lipids via pressurized CO2, but the method requires expensive, complicated hardware [35, 42]. Limitations and applications of the mentioned techniques are discussed (Table 1).

Table 1: Comparative Analysis of Different Oil Extraction Methods by Using Microalgae

Methods	Reaction conditions	Microalgae	Advantages	Limitations	References
Ultrasonic-associated extraction	Intensity of ultrasonic: 40KHz, Ultrasonic Power: 2.68 W/m²	Nannochloropsis, Chlorella vulgaris, Trichosporum,	Enhances extraction rate, Reduce the time of extraction, Fewer solvents, Great penetration into algal cells	Energy loss concerning distance, Expensive approach, Difficult to scale up	[43]
Microwave-assisted extraction	T:120°C Irradiation, Power: 880W	C.sorokiniana, N.salina, Galdieria sulphuraria	Efficient heat and mass transfer, Higher extraction yield than conventional methods	Maintenance cost is higher, Scale-up is difficult	[44]
Organic Solvent (chloroform/ methanolextraction method)	T:20°C, Light intensity: 300 µmol m <sup>-2</sup> s <sup>-1</sup>	Chlorella zofingiensis, Isochrysis galbana	High biodiesel yield, Efficient and reliable, Easy solubility of lipids	Presence of solvent residues after extraction, Some solvents are toxic	[45]
Electroporation	Treatment Intensity: 28kWh/m³, Appropriate culture conditions	Nannochloropsis salina, Chlorella vulgaris	A small amount of energy is required to use short electrical pulses, 90% lipid extraction	Intensity of field, frequency of field and geometry of electric pulses have an impact on the resulting extraction	[30]
Isotonic extraction method	T:0-140°C, Organic and inorganic ions	Chlorella sorokiniana, Chlamydomonas reinhardtii, Botryococcus braunii	lonic liquids enable synthetic flexibility, tailoring the properties of the solvent like polarity, solubility and conductivity	Energy-intensive, High cost of solvents as the solvents used are synthetic, "green"	[46]
Osmotic pressure	T: 20°C, speed: 20-25rpm	reinhardtii, Chlamydomonas reinhardtii	Economically feasible, Cost-effective, Consumes low energy	Consumes much time Generates waste salt water	[47]
Supercritical Co <sub>2</sub> extraction	Pressure: 40 MPa, T: 333K, Co₂ flow rate from 0.3 – 0.5 kg h <sup>-1</sup>	Nannochloropsis oculata, Cylindrotheca closterium, Chlorella vulgaris	Non-toxic, solvent-free lipids, consistency supports mass transfer balance.	Expensive equipments needed	[48]
Bead beating	Microscopic beads with high speed	Nannochloropsis oculata, Chlorella zofingiensis	Cost-effective, Better disruption of the cell, Extraction with high efficiency	Energy-intensive, Difficult to scale up	[49]
Enzyme-assisted extraction (cellulose, neutral protease, alkaline protease)	T:53°C, pH=4.4	Nannochloropsis Sp.Chlorella vulgaris, Scenedesmus dimorphus	Easy extraction of internal lipids, Cell disruption with minimal damage, High lipid recovery	Affected by the composition of lipid class and type, the Type and dosage of enzymes for extraction are high in cost, strongly dependent on pH	[46]
Expeller press	Dried algal biomass, High mechanical pressure to crush and extract oil	Nannochloropsis oculata, Chlorella zofingiensis, Isochrysis galbana	Solvent-free extraction, High-quality oil yield, Less oxidation	High cost, Heat generation and possible damage to the compounds	[50]

## **Transesterification Process**

Transesterification is commonly adopted as a process of converting algal oil into biodiesel. It is a reversible combination of triglycerides and surplus methanol (at a 3:1 molar proportion), yielding glycerol and methyl derivatives. The stepwise reaction occurs in three phases: triglycerides transform into diglycerides and then monoglycerides, and then into methyl esters and glycerol, with the highest yield of 98% [1]. Acids, bases (e.g., NaOH, KOH), biocatalysts (lipases), and alkoxides such as sodium methoxide are catalysts used. The catalytic reaction is four thousand times quicker in bases compared to acidic conditions, and the temperature is usually maintained at 60°C under 1 atmospheric pressure, with a time of 90 minutes [51, 16]. Methanol and oil have to be dry to prevent the formation of soap. Nevertheless, the fact that methanol does not mix easily with oil causes mass transfer problems; thus, intense mixing is necessary. Biodiesel and glycerol cannot be easily purified after the reaction because these two components separate into different phases. An essential recovery of methanol, which is beneficial in terms of costs and the environment, is obtained through flash evaporation or vacuum distillation [46,52](Figure 3).




Figure 3: Transesterification Reaction for Conversion of Lipids into Biodiesel

**DOI:** https://doi.org/10.54393/fbt.v5i3.181

# **Economic Challenges and Future Perspectives**

The microalgae are bioactive products that contain several bioactive compounds, such as lipids and carbohydrates, which can be processed through processing by enzymatic and mechanical processes to produce biodiesel efficiently. This practice is dubbed green and commercially feasible as well as time-effective. Microalgae are a third-generation feedstock and, as such, can provide an environmentally friendly alternative to fossil fuels as well as other biofuels of the first and second generation. Nevertheless, commercialization, particularly the high costs involved in the process, is its major challenge, as far as cultivation, harvesting, and the extraction of lipids are concerned. Physical and biological factors light, temperature and pH, also influence large-scale production. In the basecatalyzed transesterification process, which is most often employed, the separation and purification of biodiesel and glycerol are both complex and require vigorous mixing and repetition of the washing procedures. Vacuum distillation plays an important role in the quality of the products and the sustainability of the environment in recovering methanol [52]. Although the existing extraction methods have presently not yet been perfected, multidisciplinary studies coupled with algal genomics have opened the portals to optimal lipid synthesis and an enhanced yield in biofuels of numerous strains of algae [53]. CRISPR/Cas9 and Cas12a systems have improved editing precision and multiplexing capacity for transcriptional modulation and metabolic rerouting [53].

# CONCLUSION

Gradually increasing energy demand globally cannot be met with the usual biofuel production methods. The constant use of these sources of biofuel also changes our global carbon cycle. Algae, as an autotrophic organism, are utilized as a prospective mass production source for biofuel production. Biomolecules of algae cells, like lipids and carbohydrates, can be exploited for bioethanol and biodiesel production. In this review article, the prospects of algae as an emerging source for biofuel production for biofuel are thoroughly narrated. For research purposes, the cultivation of algae in various methods, like open and closed (photo-bioreactors) pond systems with their drawbacks, is comprehensively discussed. Solvent extraction and supercritical fluid extraction were seen as the most common methods of extraction. However, although every method has its advantages and limitation, new technological advancements lead to many new methods that will be eco-friendly, will have high efficiency, and require low maintenance costs. Still, a lot of research and development work is required for an efficient biofuel production system from algae.

# Authors Contribution

Conceptualization: NI

Methodology: NI, JI, MIR, EA, MA Formal analysis: NI, EA, AM

Writing review and editing: NI, AM, MA

All authors have read and agreed to the published version of the manuscript.

## Conflicts of Interest

All the authors declare no conflict of interest.

# Source of Funding

The authors received no financial support for the research, authorship and/or publication of this article.

# REFERENCES

- [1] Jacob A, Ashok B, Alagumalai A, Chyuan OH, Le PT. Critical Review on Third Generation Micro Algae Biodiesel Production and Its Feasibility as Future Bioenergy for IC Engine Applications. Energy Conversion and Management. 2021 Jan; 228: 113655. doi: 10.1016/j.enconman.2020.113655.
- [2] Ganesan R, Manigandan S, Samuel MS, Shanmuganathan R, Brindhadevi K, Chi NT et al. A Review on Prospective Production of Biofuel from Microalgae. Biotechnology Reports. 2020 Sep; 27: e00509.doi:10.1016/j.btre.2020.e00509.
- [3] Zhang S, Zhang L, Xu G, Li F, Li X. A Review on Biodiesel Production from Microalgae: Influencing Parameters and Recent Advanced Technologies. Frontiers in Microbiology. 2022 Jul; 13: 970028. doi: 10.3389/fmicb.2022.970028.
- [4] Mountourakis F, Papazi A, Maragkoudakis A, Stamatis N, Kotzabasis K. Evidence of Physiological Adaptation of Chlorella Vulgaris Under Extreme Salinity-New Insights into A Potential Halotolerance Strategy. Environmental and Experimental Botany. 2023 Dec; 216: 105543. doi: 10.1016/j.envexpbot.20 23.105543.
- [5] Panahi Y, Khosroushahi AY, Sahebkar A, Heidari HR. Impact of Cultivation Condition and Media Content Onchlorella Vulgaris Composition. Advanced Pharmaceutical Bulletin. 2019 Jun; 9(2): 182. doi: 10.15171/apb.2019.022.
- [6] Gao M, Ling N, Tian H, Guo C, Wang Q. Toxicity, Physiological Response, and Bio-Sorption Mechanism of Dunaliella Salina to Copper, Lead, and Cadmium. Frontiers in Microbiology. 2024 Mar; 15: 1374275. doi:10.3389/fmicb.2024.1374275.
- [7] Raslavičius L, Striūgas N, Felneris M. New Insights into Algae Factories of the Future. Renewable and Sustainable Energy Reviews. 2018 Jan; 81: 643-54. doi:10.1016/j.rser.2017.08.024.

- [8] Lam TP, Lee TM, Chen CY, Chang JS. Strategies to Control Biological Contaminants During Microalgal Cultivation in Open Ponds. Bio-resource Technology. 2018 Mar; 252: 180-7. doi: 10.1016/j.biortech.2017.12. 088.
- [9] Vecchi V, Barera S, Bassi R, Dall'Osto L. Potential and Challenges of Improving Photosynthesis in Algae. Plants. 2020 Jan; 9(1): 67. doi: 10.3390/plants9010
- [10] Demirbas A and Demirbas MF. Importance of Algae Oil as A Source of Biodiesel. Energy Conversion and Management. 2011 Jan; 52(1): 163-70. doi: 10.1016/j. enconman.2010.06.055.
- Demirbas A. Progress and Recent Trends in Biodiesel [11] Fuels. Energy Conversion and Management. 2009 Jan; 50(1): 14-34. doi: 10.1016/j.enconman.20 08.09.001.
- [12] Scott SA, Davey MP, Dennis JS, Horst I, Howe CJ, Lea-Smith DJ et al. Biodiesel from Algae: Challenges and Prospects. Current Opinion in Biotechnology. 2010 Jun; 21(3): 277-86. doi: 10.1016/j.copbio.2010.03.005.
- [13] Andeden EE, Ozturk S, Aslim B. Evaluation of Thirty Microalgal Isolates as Biodiesel Feed Stocks Based on Lipid Productivity and Triacylglycerol (TAG) content. Current Microbiology. 2021 Feb; 78(2): 775-88. doi: 10.1007/s00284-020-02340-5.
- [14] Hossain AB, Salleh A, Boyce AN, Chowdhury P, Naqiuddin M. Biodiesel Fuel Production from Algae as Renewable Energy. American Journal of Biochemistry and Biotechnology. 2008 Mar; 4(3): 250-4. doi: 10.3844/ajbbsp.2008.250.254.
- [15] Kothari R, Goria K, Bharti A, Singh HM, Pathak VV, Pathak A, Tyagi VV. Sustainable Development Goals (SDGs-7) for Bioeconomy with Bioenergy Sector. In Sustainable butanol biofuels. 2023 Apr: 29-56. doi: 10.1201/9781003165408-2.
- [16] Powar RS, Yadav AS, Ramakrishna CS, Patel S, Mohan M, Sakharwade SG et al. Algae: A Potential Feedstock for Third Generation Biofuel. Materials Today: Proceedings. 2022 Jan; 63: A27-33. doi: 10.1016/j. matpr.2022.07.161.
- [17] Mizik T and Gyarmati G. Economic and Sustainability of Biodiesel Production—A Systematic Literature Review. Clean Technologies. 2021 Jan; 3(1): 19-36. doi: 10.3390/cleantechnol3010002.
- [18] Li J, Qian J, Tang J, Jin Z, Lu Q, Cheng J et al. Enhancement of Ammonium Removal from Landfill Leachate Using Microalgae by an Integrated Strategy of Nutrient Balance and Trophic Mode Conversion. Algal Research. 2022 Jan; 61: 102572. doi: 10.1016/j. algal.2021.102572.

- [19] Debowski M, Zieliński M, Kazimierowicz J, Kujawska N, Talbierz S. Microalgae Cultivation Technologies as an Opportunity for Bioenergetic System Development-Advantages and Limitations. Sustainability. 2020 Nov; 12(23): 9980. doi: 10.3390/ su12239980.
- [20] Khan S, Naushad M, Igbal J, Bathula C, Sharma G. Production and Harvesting of Microalgae and an Efficient Operational Approach to Biofuel Production for A Sustainable Environment. Fuel. 2022 Mar; 311: 122543. doi: 10.1016/j.fuel.2021.122543.
- [21] Bhatia SK, Mehariya S, Bhatia RK, Kumar M, Pugazhendhi A, Awasthi MK et al. Wastewater Based Microalgal Biorefinery for Bioenergy Production: Progress and Challenges. Science of the Total Environment. 2021 Jan; 751: 141599. doi: 10.1016/j. scitotenv.2020.141599.
- [22] Carvalho AP, Meireles LA, Malcata FX. Microalgal Reactors: A Review of Enclosed System Designs and Performances. Biotechnology Progress. 2006; 22(6): 1490-506. doi: 10.1002/bp060065r.
- [23] Ahmed Z, Ahmad M, Caglar AE, Pinzon S. Achieving Carbon Neutrality and SDGS: Assessing Roles of Solar Energy, Government Stability, and Population Aging in Greenhouse Gas Emissions. International Journal of Sustainable Development and World Ecology. 2025 Feb; 32(2): 127-41. doi: 10.1080/135045 09.2024.2414377.
- [24] Singh J and Gu S. Commercialization Potential of Microalgae for Biofuels Production. Renewable and Sustainable Energy Reviews. 2010 Dec; 14(9): 2596-610. doi: 10.1016/j.rser.2010.06.014.
- [25] Ren X, Wei C, Yan Q, Shan X, Wu M, Zhao X et al. Optimization of a Novel Lipid Extraction Process from Microalgae. Scientific Reports. 2021 Oct 12; 11(1): 20221. doi: 10.1038/s41598-021-99356-z.
- [26] Uduman N, Qi Y, Danquah MK, Forde GM, Hoadley A. Dewatering of Microalgal Cultures: A Major Bottleneck to Algae-Based Fuels. Journal of Renewable and Sustainable Energy. 2010 Jan; 2(1). doi: 10.1063/1.3294480.
- [27] Pore SM, Sutkara PR, Walekar LS, Dhulap VP. Biofuel Generation by Macro and Micro Algae as a Renewable Energy Source: A Systematic Review. Ecology Environment and Conservation. 2022; 28: 140-5. doi: 10.53550/EEC.2022.v28i07s.024.
- [28] Lee SY, Khoiroh I, Vo DV, Senthil Kumar P, Show PL. Techniques of Lipid Extraction from Microalgae for Biofuel Production: A Review. Environmental Chemistry Letters. 2021 Feb; 19(1): 231-51. doi: 10.100 7/s10311-020-01088-5.

- [29] López-Bascón MA and De Castro ML. Soxhlet Extraction. In Liquid-Phase Extraction. 2020 Jan: 327-354. doi:10.1016/B978-0-12-816911-7.00011-6.
- [30] Tang DY, Khoo KS, Chew KW, Tao Y, Ho SH, Show PL. Potential Utilization of Bioproducts from Microalgae for the Quality Enhancement of Natural Products. Bioresource Technology. 2020 May; 304: 122997. doi:10.1016/j.biortech.2020.122997.
- [31] Hwang TY, Kin CM, Shing WL. Extraction Solvents in Microalgal Lipid Extraction for Biofuel Production: A Review. Malaysian Journal of Analytical Sciences. 2021Oct; 25(5): 728-39.
- [32] Zapata-Boada S, Gonzalez-Miquel M, Jobson M, Cuellar-Franca RM. Techno-Economic and Environmental Analysis of Algae Biodiesel Production Via Lipid Extraction Using Alternative Solvents. Industrial and Engineering Chemistry Research. 2022 Nov; 61(49): 18030-44. doi: 10.1021/acs.iecr.2c03016.
- [33] Iverson SJ, Lang SL, Cooper MH. Comparison of the Bligh and Dyer and Folch Methods for Total Lipid Determination in A Broad Range of Marine Tissue. Lipids. 2001 Nov; 36(11): 1283-7. doi: 10.1007/s11745-001-0843-0.
- [34] Tang DY, Yew GY, Koyande AK, Chew KW, Vo DV, Show PL. Green Technology for the Industrial Production of Biofuels and Bioproducts from Microalgae: A Review. Environmental Chemistry Letters. 2020 Nov; 18(6): 1967-85. doi: 10.1007/s10311-020-01052-3.
- [35] Mendes RL, Reis AD, Palavra AF. Supercritical CO2 Extraction of Γ-Linolenic Acid and Other Lipids from Arthrospira (Spirulina) Maxima: Comparison with Organic Solvent Extraction. Food Chemistry. 2006 Jan; 99(1): 57-63. doi: 10.1016/j.foodchem.2005.07.
- [36] Chisti Y. Biodiesel from Microalgae. Biotechnology Advances. 2007 May; 25(3): 294-306. doi: 10.1016/j. biotechadv.2007.02.001.
- [37] Lee AK, Lewis DM, Ashman PJ. Disruption of Microalgal Cells for the Extraction of Lipids for Biofuels: Processes and Specific Energy Requirements. Biomass and Bioenergy. 2012 Nov; 46:89-101. doi: 10.1016/j.biombioe.2012.06.034.
- [38] Cravotto G, Boffa L, Mantegna S, Perego P, Avogadro M, Cintas P. Improved Extraction of Vegetable Oils Under High-Intensity Ultrasound and/or Microwaves. Ultrasonics Sonochemistry. 2008 Jul; 15(5): 898-902. doi: 10.1016/j.ultsonch.2007.10.009.
- [39] Grima EM, Belarbi EH, Fernández FA, Medina AR, Chisti Y. Recovery of Microalgal Biomass and Metabolites: Process Options and Economics. Biotechnology Advances. 2003 Jan; 20(7-8): 491-515.

- doi: 10.1016/S0734-9750(02)00050-2.
- [40] Harris J, Viner K, Champagne P, Jessop PG. Advances in Microalgal Lipid Extraction for Biofuel Production: A Review. Biofuels, Bioproducts and Biorefining. 2018 Nov; 12(6): 1118-35. doi: 10.1002/bbb.1923.
- [41] Halim R, Danquah MK, Webley PA. Extraction of Oil from Microalgae for Biodiesel Production: A Review. Biotechnology Advances. 2012 May; 30(3): 709-32. doi:10.1016/j.biotechadv.2012.01.001.
- [42] Mercer P and Armenta RE. Developments in Oil Extraction from Microalgae. European Journal of Lipid Science and Technology. 2011 May; 113(5): 539-47. doi: 10.1002/ejlt.201000455.
- [43] Araujo GS, Matos LJ, Fernandes JO, Cartaxo SJ, Gonçalves LR, Fernandes FA et al. Extraction of Lipids from Microalgae by Ultrasound Application: Prospection of the Optimal Extraction Method. Ultrasonics Sonochemistry. 2013 Jan; 20(1): 95-8. doi:10.1016/j.ultsonch.2012.07.027.
- [44] Pan J, Muppaneni T, Sun Y, Reddy HK, Fu J, Lu X et al. Microwave-Assisted Extraction of Lipids from Microalgae Using an Ionic Liquid Solvent [BMIM][HSO4]. Fuel. 2016 Aug; 178: 49-55. doi: 10.101 6/j.fuel.2016.03.037.
- [45] Chen W, Liu Y, Song L, Sommerfeld M, Hu Q. Automated Accelerated Solvent Extraction Method for Total Lipid Analysis of Microalgae. Algal Research. 2020 Oct; 51: 102080. doi: 10.1016/j.algal.2020.1020 80.
- [46] Ranjith Kumar R, Hanumantha Rao P, Arumugam M. Lipid Extraction Methods from Microalgae: A Comprehensive Review. Frontiers in Energy Research. 2015 Jan; 2: 61. doi: 10.3389/fenrg.2014. 00061.
- [47] Zulqarnain, Ayoub M, Yusoff MH, Nazir MH, Zahid I, Ameen M, Sher F et al. A Comprehensive Review on Oil Extraction and Biodiesel Production Technologies. Sustainability. 2021 Jan; 13(2): 788. doi: 10.3390/su13 020788.
- [48] Mouahid A, Crampon C, Toudji SA, Badens E. Supercritical CO<sub>2</sub> Extraction of Neutral Lipids from Microalgae: Experiments and Modelling. The Journal of Supercritical Fluids. 2013 May; 77: 7-16. doi: 10.1016 /i.supflu.2013.01.024.
- [49] Zhou J, Wang M, Saraiva JA, Martins AP, Pinto CA, Prieto MÁ et al. Extraction of Lipids from Microalgae Using Classical and Innovative Approaches. Food Chemistry. 2022 Jan. doi: 10.1016/j.foodchem.20 22.132236.
- [50] Mubarak M, Shaija A, Suchithra TV. A Review on the Extraction of Lipid from Microalgae for Biodiesel Production. Algal Research. 2015 Jan; 7: 117-23. doi:

**DOI:** https://doi.org/10.54393/fbt.v5i3.181

- 10.1016/j.algal.2014.10.008.
- [51] Bharathiraja B, Chakravarthy M, Kumar RR, Yuvaraj D, Jayamuthunagai J, Kumar RP et al. Biodiesel Production Using Chemical and Biological Methods-A Review of Process, Catalyst, Acyl Acceptor, Source and Process Variables. Renewable and Sustainable Energy Reviews. 2014 Oct; 38: 368-82.doi:10.1016/j.rser.2014.05.084.
- [52] Chang CH, Wei HY, Chen BY, Tan CS. In Situ Catalyst-Free Biodiesel Production from Partially Wet Microalgae Treated with Mixed Methanol and Castor Oil Containing Pressurized CO2. The Journal of Supercritical Fluids. 2020 Mar; 157: 104702. doi: 10.1016/j.supflu.2019.104702.
- [53] Dhokane D, Shaikh A, Yadav A, Giri N, Bandyopadhyay A, Dasgupta S et al. CRISPR-Based Bioengineering in Microalgae for Production of Industrially Important Biomolecules. Frontiers in Bioengineering and Biotechnology. 2023 Oct; 11: 1267826. doi: 10.3389/fbioe.2023.1267826.